RAB DESIGN

VCS100CG WEATHER PROOF

The VCS100CG fixture is weather proof rated for use indoors or outdoors. Great for use in industrial applications or for residential and commercial applications where you want an industrial look with a bit of flair with a painted finish and coloured glass. For custom versions of this and other weather proof fixtures please visit our web site and look under architectural in the products section.

MOUNTING HUB Precision die cast with hub threaded for 1/2" NPT pipe

SOCKET Porcelain, medium base, 4KV pulse rated socket with a nickle-plated screw shell and a spring-loaded centre contact.

GLOBE Standard unit comes with clear globe, also available are clear prismatic, frosted and coloured globes. There are two types of coloured globes available. The GL glass is painted on the inside. The second type of glass is the RGL series, which has a more brilliant colour. This is achieved by having the colour added while the glass is being made. Both types of glass are available in the following colours amber, blue, green, red and white.

GUARD Die cast, threaded with set screw for locking guard in place.



MAXIMUM WATTAGE 100 watt incandescent.

APPROVAL CSA

LAMP Not included

FINISH Standard finish is raw. Also available with a powder coat paint finish. Some of the most common colours are black, red, white and blue. For other colours please consult factory.



www.rabdesign.ca

VCS GL100 - CLEAR GL100CL-RIB - PRISMATIC GL100SB - FROSTED PAINTED GLOBES GL100A - AMBER GL100G - GREEN GL100R - RED	3.875" 9.84cm 1.375" 3.5cm
GLOBE GL100B - BLUE RGL GLOBES RGL100A - AMBER RGL100G - GREEN RGL100B - BLUE IF RAW FINISH LEAVE BLANK BLK - BLACK RD - RED WH - WHITE BL - BLUE CC - CUSTOM COLOUR CG CG - CAST GUARD	9.625" 24.45cm
GL100 GL100CL-RIB GL100SB PRISMATIC FROSTED	GL100G GREENGL100A AMBERGL100B BLUEGL100R REDImage: Green of the state
RGL100A AMBER RGL100G GREEN	RGL100R REDRGL100B BLUEImage: State of the st

RAB DESIGN Lighting Inc. • 222 Islington Ave., Toronto, ON M8V 3W7 • TEL. 416-252-9454 / 800-268-0381 • FAX. 416-252-3046, 800-668-5517