

Date:	Project Name:
Туре:	Part Number:



DESCRIPTION

Brighten your living room, kitchen, or bathroom with the Brilliance Series recessed pot lights. With its multi-CCT feature, you can easily adjust the lighting ambiance to suit your preference. The round design and white finish blend seamlessly with any decor, providing a modern and clean aesthetic. Easy installation with high-quality mounting spring, quick connectors, and included junction box. The premium aluminum body of this LED slim panel ensures superior durability and aesthetics compared to plastic options. Say goodbye to yellowing with age.

FEATURES

- IC-rated and Air-Tight ready and may be in direct contact with insulation
- Compatible with Soffit installations and can be installed in shallow plenum spaces
- Multi CCT
- Flicker-free 120V forward-phase Triac dimming down to 10%
- 277-347V Driver Available
- FT4-Rated Cable
- Damp location
- Energy-Star, JA8 compliant
- Rated Lifetime L70(hrs): >50,000
- **CRI 80**
- 5 year warranty













Residential





Date:	Project Name:
Туре:	Part Number:

SPECIFICATION

ORDER#	MODEL#	WATTS	SIZE	VOLTAGE (V)	LUMENS	CCT (K)	BEAM ANGLE
R36008	RENO-3-S6W-345KWH	6W	3″	120V	400 lm	30/40/50K	108°
R36013	RENO-4-S12W-MCCT-WH	12W	4″	120V	800 lm	27/30/35/40/50K	108°
R36014	RENO-4-S12W-MCCT-BK	12W	4″	120V	800 lm	27/30/35/40/50K	108°
R36010	RENO-6-S12W-345KWH	12W	6″	120V	800 lm	30/40/50K	108°
R36012	RENO-8-S22W-345KWH	22W	8″	120V	1640 lm	30/40/50K	108°


ACCESSORIES


ORDER#	MODEL#	DESCRIPTION		
R39105	LED-HBL015-347V-D	AC277V-347V Driver for slim panel light 4"& 6"non dimmable		
R39106	LED-HBL033-347V-D	AC277V-347V Driver for slim panel light 8"non dimmable		
R39101	RENO-4-GR	4" Goof Ring outside Ø 5 3/4"		
R39102	RENO-6-GR	6" Goof Ring outside Ø 8"		
R39103	RENO-8-GR	8″ Goof Ring Ø 9 1/2″		
R39108	RENO-MP4	4" Mounting Plate without clip (Opening 108mm)		



Date:	Project Name:
Туре:	Part Number:

DIMENSIONS





MODEL	А	В	С	D
3″	Ø 95mm (Ø 3.75″)	Ø 57mm (Ø 2.25")	Ø 76mm (Ø 3")	Ø 25mm (Ø 1")
4"	Ø 127mm (Ø 5")	Ø 76mm (Ø 3")	Ø 101mm (Ø 4")	Ø 25mm (Ø 1")
6"	Ø 177mm (Ø 7")	Ø 127mm (Ø 5″)	Ø 158mm (Ø 6.25")	Ø 25mm (Ø 1")
8″	Ø 229mm (Ø 9")	Ø 159mm (Ø 6.25″)	Ø 210mm (Ø 8.25")	Ø 25mm (Ø 1″)