

Date:

Type:

Project Name:

Part Number:

## LED SLIM POTLIGHT



## FEATURES

- IC-rated and Air-Tight ready and may be in direct contact with insulation
- Can be installed in shallow plenum spaces
- Multi CCT Switchable (3000/4000/5000K)
- Flicker-free 120V forward-phase Triac dimming down to 5%
- 277-347V Driver Available
- 50,000 hours lifespan
- 5-year warranty

## APPLICATIONS

- Office Lighting
- Commercial Applications
- Damp & Wet location Installation
- Residential

## SPECIFICATION

ORDER #	MODEL#	BEAM ANGLE	LUMENS OUTPUT	WATTS	VOLTS	SIZE	CCT	CRI
R36008	RENO-3-S6W-345KWH	120°	400lm	6W	120V	3"	3000/4000/5000K	80
R36009	RENO-4-S9W-345KWH	120°	600lm	9W	120V	4"	3000/4000/5000K	80
R36010	RENO-6-S12W-345KWH	120°	800lm	12W	120V	6"	3000/4000/5000K	80
R36012	RENO-8-S22W-345KWH	120°	1640lm	22W	120V	8"	3000/4000/5000K	80

## ACCESSORY INFORMATION

ORDER #	MODEL#	DESCRIPTION
R39105	LED-HBL015-347V-D	AC277V-347V Driver for slim panel light 4" & 6" non dimmable
R39106	LED-HBL033-347V-D	AC277V-347V Driver for slim panel light 8" non dimmable
R39101	RENO-4-GR	4" Goof Ring outside Ø 5 3/4"
R39102	RENO-6-GR	6" Goof Ring outside Ø 8"
R39103	RENO-8-GR	8" Goof Ring outside Ø 9 1/2"



Date:	Type:
Project Name:	Part Number:

**DIMENSION**

