

Date:	Type:
Project Name:	Part Number:

## LAMPS A-TYPE



## FEATURES

- Energy Star Listed
- Smooth dimming with existing dimmers
- No UV or IR radiation
- Mercury Free
- 60W incandescent equivalent
- Elegant and Efficient Design
- 25,000 hours lifespan
- 5-year warranty

## APPLICATIONS

- General Lighting
- Recessed Down Lights
- Outdoor lighting
- Track Lights
- Damp Location Installation



## SPECIFICATION

ORDER #	MODEL#	BASE TYPE	LUMENS OUTPUT	LUMINOUS EFFICACY	BEAM ANGLE	EQUIVALENT WATTAGE	WATTS	INPUT WATTAGE	POWER FACTOR	CCT	CRI
R22101	RENOA19-9.5W-3000K-GU24-ES	GU24	800lm	94 lm/W	330°	60W	9.5W	120V AC	0.9	3000K	≥ 80
R22102	RENOA19-9.5W-4000K-GU24-ES	GU24	800lm	94 lm/W	330°	60W	9.5W	120V AC	0.9	4000K	≥ 80
R22001	RENOA19-5.5W-3000K-ES-POP	E26	450lm	82 lm/W	330°	40W	5.5W	120V AC	0.9	3000K	≥ 80
R22002	RENOA19-5.5W-4000K-ES-POP	E26	450lm	82 lm/W	330°	40W	5.5W	120V AC	0.9	4000K	≥ 80
R22003	RENOA19-5.5W-5000K-ES-POP	E26	450lm	82 lm/W	330°	40W	5.5W	120V AC	0.9	5000K	≥ 80
R22014	RENOA19-8.5W-3000K-ES-POP	E26	800lm	94 lm/W	330°	60W	8.5W	120V AC	0.9	3000K	≥ 80
R22015	RENOA19-8.5W-4000K-ES-POP	E26	800lm	94 lm/W	330°	60W	8.5W	120V AC	0.9	4000K	≥ 80
R22016	RENOA19-8.5W-5000K-ES-POP	E26	800lm	94 lm/W	330°	60W	8.5W	120V AC	0.9	5000K	≥ 80
R22008	RENOA19-15.5W-3000K	E26	1600lm	107 lm/W	330°	100W	15.5W	120V AC	0.9	3000K	≥ 80
R22009	RENOA19-15.5W-5000K	E26	1600lm	107 lm/W	330°	100W	15.5W	120V AC	0.9	5000K	≥ 80

