

S11908

7W/LED/T5/840/BP

7 watt T5 LED; Miniature bi-pin base; 4000K; 50000 Average rated hours; 700 lumens; 120-277 volts



Features

- No ballast or external driver required
 Available in 6", 9", 12", & 21"
- Available in 6, 9, 12, & 21
 Direct wire 120-277V line voltage
 Double ended wiring
 NSF Approved
 PET Shatterproof coated
 5 year Limited warranty

S11908

Replaces F13T5/CW lamps

Item Number	UP	UPC		Watts	Operating Frequency		rescent uivalent		ower actor	Lamp Shape	
S11908	0459231	045923119088		7	50/60Hz		13W		0.90	T5	
Base	ANSI Base	Lam	p Code	D	Dimmable/Non- Dimmable		MOL In Inches		OD In nches	Initial Lumens	
Miniature Bi- Pin	G5	7W/LED	/T5/840/BP	N	Ion-Dimmable	Frosted	20-29/32'	-29/32" 0		700	
Average Rated Hours	d Kelvi Tem	Cold	or CRI	Beam Sp Deg	· Operating 16		ature	Pack	CE	C Status	
50000	4000 Co Wh		80	240	,	-25C (-13F) to a maximum of +45C (+113F)		10	Lawful for sale in California		
Material	RoHS Compliant		UL or E	TL Listed	UI	UL Classification			Warranty		
Glass	Yes		`	Yes	cULus Classified - Damp Location Rated				5 Year Limited		



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051