

Project Name

Location

Prepared By



## SATCO S11922

13.5T8/LED/48-840/DIM-BP

### Notes

### General

Status	Active
Watts	13.5
Volts	120V
Ballast Type	Type B
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Frosted
CCT (Kelvin)	4000
Temperature	Cool White
CRI	82
Lumens	1800
Beam Spread	220
Dimmable	Yes Dimmable
Hours Rated	50000
Lamp Type	Linear
Technology	LED

### Electrical

Ballasting Requirements	Ballast Bypass; Direct wire 120V line voltage; No ballast or external driver required
Dimmable Down To	< 10 %
Power Factor	0.9
Operating Temperature	-20C (-4F) to a maximum of +45C (+113F)

### Physical

MOL	48
MOD	1
Lens Finish	Frosted
Lens Material	Glass
Housing Color	White

### Additional Information

Additional Info	All glass tube
Tube Guard Use	Approved for use with tube guards
Installation Notes	Install only in non-shunted lampholders
Warranty	5 Year Limited - T8 LED Bulbs - Ballast Bypass

### Compliance

Safety Listing	cULus Classified
Location Rating	Damp
Energy Star	No
DLC Approved	Yes
DLC ID	PLCHL8NP6U2O
CEC Status	Lawful for sale in California
RoHS Compliant	Yes

FCC Compliant	Yes
NSF Approved	Yes - Approved

