

Project Name

Location

Prepared By



SATCO S21410

9PL/LED/HV/5CCT/A+B/G24Q

Notes

[www] 10-02-2023 00:24:50

General

| | |
|------------------------|-------------------------------|
| Status | Active |
| Watts | 9W |
| Fluorescent Equivalent | 26W |
| Volts | 120V-277V |
| Ballast Type | Type A/B |
| Shape | PL |
| Base | G24q (4-Pin) |
| ANSI Base | G24q-4 |
| Finish | White |
| CCT (Kelvin) | 2700K/3000K/3500K/4000K/5000K |
| Temperature | Warm White to Natural Light |
| CRI | 82 |
| Lumens | 1100L |
| Beam Spread | 120 |
| Dimmable | Yes-Dimmable |
| Hours Rated | 50000 |
| Lamp Type | PL 4-Pin |
| Operating Position | Universal |
| Technology | LED |

Electrical

| | |
|-----------------------|--|
| Operating Frequency | 50/60Hz |
| Dimming Note | Only Dimmable with Compatible Dimming Ballasts |
| Power Factor | 0.9 |
| THD | 20% |
| Operating Temperature | -20C (-4F) to +45C (+113F) |

Physical

| | |
|---------------|-------|
| MOL | 6.76 |
| MOD | 2.36 |
| Housing Color | White |
| Weight (lb.) | 0.4 |

Additional Information

| | |
|----------------------------|---|
| Installation Notes | Suggested wattage equivalency = 26W CFL |
| Rated For Enclosed Fixture | No |
| Warranty | 5 Year Limited - 10 hr per day |

Compliance

| | |
|------------------------|------------------------------------|
| Safety Listing | cULus - Listed; cULus - Classified |
| Location Rating | Damp |
| DLC Approved | Yes |
| DLC ID | S-GE9ZMN; S-K73DCJ |
| Air Tight Rated | No |
| NSF Approved | Yes |
| CA T20 / T24 Rationale | Exempt - Base Not Regulated |
| California Status | Lawful for sale in California |
| Title 20 / 24 Status | Lawful for sale |
| RoHS Compliant | Yes |
| SDS Sheet | LED_Lamp |

