

S29860

9WPLV/LED/840/DR/4P

9W LED PL 4-Pin; 4000K; 1000 Lumens; G24q base; 50000 Average rated hours; 120 Deg. beam spread

Features

- Replaces 26, 32, and 42 watt CFLs
- Direct Replacement for use with Electronic, Instant Start, Rapid Start, and Programmed Start ballasts with no rewiring required. Ballast required.
- Instant on to full brightness / no flickering
- Vertical operation
- Up to 70% energy saving
 Long life 50,000 hours
- 5 year warranty

*Ballast required (See Ballast Compatibility Chart)

View: Ballast Compatibility Chart

Emergency Ballast Compatibility Chart

-	_	P

S29860

Item Number	UPC	Watts		rescent iivalent	Lamp Shape	Base	Lamp Code		Dimmable/Non- Dimmable			
S29860	045923298608	9	· ·	2, and 42 tt CFL	PL	G24q	9WPLV/LED/840/DR/4P			Non-Dimmable		
Finish	MOL In Inches	MOD In		Initial Lum		Average		Hours		in Temp	Color	CRI
Frost	4-11/16"	1-15/	16"	1000		50000			4	000	Cool White	82
Beam Spread Deg	Operating Temperature		kage ype	CEC Status	S	DLC ID:		RoH Compl		UL or ETL Listed	UL Classific	cation
120	-20C (-4F) to a maximum of +450 (+113F)	СВ	lox	Lawful for sale in California	PLZ5IXXDQS03 Yes		Yes	cULus Classified - Damp Location Rated				
Warranty												
<u>5 Year Limited</u>												



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051