

## S29912

25T5/LED/46-835/DR 25 watt T5 LED; Miniature bi-pin base; 3500K; 50000 Average rated hours; 3300 lumens

## Features

- Direct Replacement for use on Electronic ballasts with no rewiring required\*
- Replaces F54T5/HO linear fluorescent lamps
- High efficacy
- NSF Approved
- Integrated thermal fuse at pins
  5 year Limited warranty

\*May not be compatible with all rapid start ballasts.

Ballast required

View: **Ballast Compatibility Chart** 

SATCO' 2754.02044-0500R Couple of materials SM 2000LH Science		1000 m 1.100 m 1.
	S29912	

Item Number	l	UPC	Watts	Fluorescent Equivalent		.amp Shape		Base	ANS Bas		L	.amp	Code
S29912	04592	232991	24 25	54W		T5	Mini	iature Bi- Pin	G	5	25T5/	LED/	46-835/DR
Finish	MOL In	Inches	Initial Lumens	Average Rated Ho	ours	Kelvin T	emp	Co	lor	CF	RI Be	am S	pread Deg
Gloss White	48	8''	3300	50000		3500	0	Neutral	White	82	2		185
Operati Tempera	9	Pack	CEC Status	DLC ID:		RoHS compliant	l	JL or ETL .isted	UL Cla	assifi	cation		Warranty
-20C (-4F) maximum o (+113F	f +45C	10	Lawful for sale in California	PLF2500Z49X9 DLC Search		Yes		Yes [	cULus Damp Lo				<u>5 Year</u> Limited



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051