

Project Name

Location

Prepared By



**Notes**

[www] 09-21-2020 03:40:10

**General**

Status	Active
Watts	40
Incandescent Equivalent	300
Fluorescent Equivalent	65
HID Equivalent	175
Volts	100V-277V
Shape	Comcob
Base	Mogul Extended
ANSI Base	EX39
Finish	Clear
CCT (Kelvin)	5000
Temperature	Natural Light
CRI	80
Lumens	5600
Beam Spread	120;150;260
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	LED HID
Technology	LED
Min Compartment Size	Width: 8.00 in. Depth: 8.00 in. Height: 11.00 in.

**Electrical**

Operating Frequency	50/60 Hz
Power Factor	>0.9
Surge Protection	Built-in surge protection - 4KV
THD	<20%
Operating Temperature	-20C (-4F) to a maximum of +65C (+149F)

**Physical**

MOL	7.24
MOD	3.35
Housing Color	White
Photocell	Optional Add-On
Weight (lb.)	1.85

**Additional Information**

Additional Info	PIR Sensor available as an accessory
Enclosure Rating	Enclosed Rated Lamp
Rated For Enclosed Fixture	Yes
IP Rating	IP64
Specification Note	Closed 260 deg; Partial 150 deg; Open 120 deg
Warranty	5 Year Limited - Hi-Pro

**Compliance**

Safety Listing	cULus Classified
Location Rating	Damp

Energy Star	No
DLC Approved	Yes
DLC ID	PLISIESIO4OC
CEC Status	Lawful for sale in California
RoHS Compliant	Yes
SDS Sheet	LED_Lamp

