

Project Name

Location

Prepared By



SATCO S9281

3MR11/LED/25/3000K/12V

Notes

General

| | |
|-------------------------|--------------|
| Status | Active |
| Watts | 3 |
| Incandescent Equivalent | 20 |
| Volts | 12V |
| Shape | MR11 |
| Base | Bi Pin GU4 |
| ANSI Base | GU4 |
| Finish | Lensed |
| CCT (Kelvin) | 3000 |
| Temperature | Warm White |
| CRI | 80 |
| Lumens | 210 |
| Beam Spread | 25 |
| Dimmable | Non-Dimmable |
| Hours Rated | 25000 |
| Technology | LED |

Electrical

| | |
|-----------------------|--|
| Candlepower | 700 |
| Spot Type | NFL - Narrow Flood |
| Dimmable Down To | N/A |
| Dimming Type | N/A |
| Power Factor | 0.65 |
| Operating Temperature | -25C (-13F) to a maximum of +45C (+113F) |

Physical

| | |
|---------------|-------|
| MOL | 1.5 |
| MOD | 1.38 |
| Housing Color | White |

Additional Information

| | |
|------------------|--------------------------------|
| Enclosure Rating | Enclosed Rated Lamp |
| Warranty | 5 Year Limited - 10 hr per day |

Compliance

| | |
|-----------------|-------------------------------|
| Safety Listing | cULus |
| Location Rating | Damp |
| Energy Star | No |
| CEC Status | Lawful for sale in California |
| RoHS Compliant | Yes |
| SDS Sheet | LED_Lamp |