

S9394

54W/LED/HID/5000K/100-277V 54 watt - LED HID Replacement; 5000K; Mogul extended base; 100-277 volts

Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
 Ballast by-pass Direct wire only 100V 277V
 UL approved for totally enclosed fixtures
 Damp location IP65 rated

- For outdoor & indoor use
- DLC Listed
- Base up or base down operation (high/low bay and post top)
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- Classified under UL 1598C

Additional Technical Specifications

- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60Hz
- Working Voltage AC90-305V

Minimum Compartment Size						
Length	Width	Depth				
17.3 inch	9.25 inch	9.25 inch				

Optional accessory: In-line surge protector 80-929

This item has been discontinued. Possible replacement:

• S29394



S9394

Item Number	Product Line	UPC	Input Voltage Watts		Incandescent Equivalent	Fluorescent Equivalent	HID Equivalent
S9394	Hi-Pro	045923093944	100 - 277	54	300W	85W	250W

Base	ANSI Base		Lamp Code			Dimmable/Non- Dimmable		Finish	MOL In Inches	MOD Ir Inches	
Mogul Extended	EX39	54W/L	ED/HID/5000	ED/HID/5000K/100-277V			Non-Dimmable White		10-3/4"	3.69"	7200
Average Rated Hours		elvin emp	Color	CRI		Spread Deg	Operati	ng Tempe	rature	Pack	Package Type
50000	5	5000	Natural Light	80+	3	.300		F) to a maximum of -65C (+149F)		12	Box
CEC Status D		LC ID:	RoHS Complia	nt	UL or ETL Listed	UL Cla	ssification	Warranty	y Sta	atus	Suggested Substitute
Lawful for sale in California	P7RMM PMM9N DLC Se	X2Z	Yes		Yes		- Damp on Rated	5 Year Limited	Discor	ntinued	<u>S29394</u>

Dimmable/Non-



ANSI

National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com

Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico

Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051

MOL In

MOD In

Initial