



# S9711

25T5/LED/46-850/DR

25 watt T5 LED; Miniature bi-pin base; 5000K; 50000 average rated hours; 3200 lumens



## Features

- Direct Replacement - for use on Electronic Instant Start and Rapid Start ballasts with no rewiring required\*
- Ballast required
- Solid State LED lighting
- High efficacy
- Long life
- 54watt Fluorescent equivalency
- Approved for enclosed luminaires
- 5 year Limited warranty

S9711

\*May not be compatible with all instant start ballasts.

View:

[Ballast Compatibility Chart](#)

This item has been discontinued.

Possible replacement:

- [S9911](#)

Item Number	UPC	Watts	Fluorescent Equivalent	Lamp Shape	Base	ANSI Base	Lamp Code
S9711	045923097119	25	54W	T5	Miniature Bi-Pin	G5	25T5/LED/46-850/DR
Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp	Color
Non-Dimmable	White	48"	0.625"	3200	50000	5000	Natural Light
CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type	RoHS Compliant	UL or ETL Listed	UL Classification
82	185	-20°C (-4°F) to a maximum of +45°C (113°F)	10	Box	Yes	Yes	cULus Classified - Damp Location Rated
Warranty		Status			Suggested Substitute		



National Toll-Free:  
800.43.SATCO  
(800.437.2826)  
[www.satco.com](http://www.satco.com)

Distribution Centers:  
New York, Florida, Texas,  
Washington, California,  
Puerto Rico

Corporate Offices:  
110 Heartland Blvd.,  
Brentwood, NY 11717  
800.437.2826 631.243.2022  
Fax 631.243.2027

