



# S9751

40W/LED/HID/MB/5000K/100-277V  
 40 watt - LED HID Replacement; 5000K; Mogul extended base;  
 100-277 volts

### Features

- Replaces HID, CFL, and Incandescent
- Direct wire range voltage 100-277V
- Approved for totally enclosed fixtures
- Hi bay, low bay and post top
- Light panels lock into place creating 3 separate beam angle options
- IP65 rated
- 5 year limited warranty

Specification note: Power Factor >0.9; Operating temperature range -20°C to 65°C; Operating Frequency 50-60Hz; Working Voltage AC 90-305V

Optional accessory: In-line surge protector [80-929](#)

Width (360°)	Width (270°)	Width (180°)
3.5"	7.7"	8.9"

Minimum Compartment Size		
Length	Width	Depth
8.27 inch	9.25 inch	9.25 inch

This item has been discontinued.  
 Possible replacement:

- [S29751](#)



S9751

Item Number	Product Line	UPC	Input Voltage	Watts	Incandescent Equivalent	Fluorescent Equivalent	HID Equivalent
-------------	--------------	-----	---------------	-------	-------------------------	------------------------	----------------

S9751	Hi-Pro	045923097515	100 - 277	40	300W	65W	175W	
Power Factor	Base	ANSI Base	Lamp Code		Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches
0.90	Mogul Extended	EX39	40W/LED/HID/MB/5000K/100-277V		Non-Dimmable	White	7-7/8"	3-1/2" (Open 8-7/8")
Initial Lumens	Average Rated Hours	Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature		Pack
5200	50000	5000	Natural Light	80+	Adjustable: 360; 270; 180	-20C (-4F) to a maximum of +65C (+149F)		12/6
Package Type	CEC Status	RoHS Compliant	Fixture Type	UL or ETL Listed	UL Classification	Warranty	Status	Suggested Substitute
Box	Lawful for sale in California	Yes	Enclosed Rated	Yes	cULus - Damp Location Rated	<a href="#">5 Year Limited</a>	Discontinued	<a href="#">S29751</a>



National Toll-Free:  
800.43.SATCO  
(800.437.2826)  
[www.satco.com](http://www.satco.com)

Distribution Centers:  
New York, Florida, Texas,  
Washington, California,  
Puerto Rico

Corporate Offices:  
110 Heartland Blvd.,  
Brentwood, NY 11717  
800.437.2826 631.243.2022  
Fax 631.243.2027

