



# S9768

30W/LED/HID/MB/2700K/100-277V  
 30 watt - LED HID Replacement; 2700K; Medium base;  
 Adjustable beam angle; 100-277 volts

### Features

- Replaces HID, CFL, and Incandescent
- Direct wire range voltage 100-277V
- Approved for totally enclosed fixtures
- Hi bay, low bay and post top
- Light panels lock into place creating 3 separate beam angle options
- IP65 rated
- 5 year limited warranty

Specification note: Power Factor >0.9; Operating temperature range -20°C to 65°C; Operating Frequency 50-60Hz; Working Voltage AC 90-305V

Optional accessory: In-line surge protector [80-929](#)

| Width (360°) | Width (270°) | Width (180°) |
|--------------|--------------|--------------|
| 3.2"         | 6.8"         | 7.7"         |

| Minimum Compartment Size |        |        |
|--------------------------|--------|--------|
| Length                   | Width  | Depth  |
| 11 inch                  | 8 inch | 8 inch |



S9768

| Item Number | Product Line | UPC          | Input Voltage | Watts | Incandescent Equivalent | Fluorescent Equivalent | HID Equivalent |
|-------------|--------------|--------------|---------------|-------|-------------------------|------------------------|----------------|
| S9768       | Hi-Pro       | 045923097683 | 100 - 277     | 30    | 200W                    | 55W                    | 150W           |

| Power Factor | Base   | ANSI Base | Lamp Code                     | Dimmable/Non-Dimmable | Finish | MOL In Inches | MOD In Inches              |
|--------------|--------|-----------|-------------------------------|-----------------------|--------|---------------|----------------------------|
| 0.90         | Medium | E26       | 30W/LED/HID/MB/2700K/100-277V | Non-Dimmable          | White  | 6-3/8"        | 3-3/16"<br>(Open 7-11/16") |

| Initial Lumens | Average Rated Hours | Kelvin Temp | Color | CRI | Beam Spread Deg | Operating Temperature | Pack |
|----------------|---------------------|-------------|-------|-----|-----------------|-----------------------|------|
|----------------|---------------------|-------------|-------|-----|-----------------|-----------------------|------|

| 3660         | 50000                         | 2700           | Warm White     | 83               | Adjustable: 360; 270; 180   | -20C (-4F) to a maximum of +65C (+149F) | 24/6 |
|--------------|-------------------------------|----------------|----------------|------------------|-----------------------------|---|------|
| Package Type | CEC Status                    | RoHS Compliant | Fixture Type   | UL or ETL Listed | UL Classification           | Warranty                                |      |
| Box          | Lawful for sale in California | Yes            | Enclosed Rated | Yes              | cULus - Damp Location Rated | <a href="#">5 Year Limited</a>          |      |



**National Toll-Free:**  
 800.43.SATCO  
 (800.437.2826)  
[www.satco.com](http://www.satco.com)

**Distribution Centers:**  
 New York, Florida, Texas,  
 Washington, California,  
 Puerto Rico

**Corporate Offices:**  
 110 Heartland Blvd.,  
 Brentwood, NY 11717  
 800.437.2826 631.243.2022  
 Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051