



S9779

40W/LED/HID/PT/3000K/100-277V
 40 watt - Post Top LED; 3000K; Medium base; 100-277 volts

Features

- For use in any post top fixture to provide light out and down only
- Replaces HID, CFL, and Incandescent
- Direct wire range voltage 100-277V

Specification note: Operating temperature range -20°C to 65°C;
 Operating Frequency 50-60Hz; Working Voltage AC 90-305V

Minimum Compartment Size		
Length	Width	Depth
9.25 inch	9.25 inch	8.27 inch



S9779

Optional accessory: In-line surge protector [80-929](#)

Item Number	Product Line	UPC	Input Voltage	Watts	Operating Frequency	Base	ANSI Base
S9779	Hi-Pro	045923097799	100 - 277	40	50/60Hz	Medium	E26
Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp
40W/LED/HID/PT/3000K/100-277V	Non-Dimmable	White	5-1/2"	5-1/8"	5000	50000	3000
Color	CRI	Operating Temperature	Pack	Package Type	CEC Status	RoHS Compliant	UL or ETL Listed
Soft White	80+	Operating temperature: -20°C (-4°F) to a maximum of +45°C (113°F)	12	Box	Lawful for sale in California	Yes	Yes
UL Classification						Warranty	
cULus - Damp Location Rated						5 Year Limited	



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027

