



# PRO Line Family of LED Lamps

**15,000 HOURS • 3 YEAR WARRANTY**

For an affordable LED upgrade, switch to TCP's PRO line family of LED Lamps. The PRO line family of LEDs are available in multiple options from A-Lamps, to BR30 and PAR38 lamps. See how you can maximize savings and minimize maintenance cost with Pro LEDs.

## LIMITLESS OPTIONS FOR THE FOLLOWING APPLICATIONS

- Commercial
- Retail
- Healthcare
- Industrial
- Residential

### FEATURES

- Long life: 15,000 hours
- Very low heat generation
- UL approved for damp location\*
- Inexpensive
- ANSI Construction Compliant

### BENEFITS

- Minimizes replacement and maintenance costs
- Perfect for sensitive display lighting such as art galleries
- Can be used outdoors when protected from elements—withstands humidity indoors/outdoors
- Save on cost
- Fits most general appliances

\*All PAR lamps are suitable for wet locations

## SPECIFICATIONS

|                              |                     |
|------------------------------|---------------------|
| Color Temperatures .....     | 2700K, 3000K, 5000K |
| Input Line Voltage .....     | 120 VAC             |
| Input Line Frequency .....   | 50/60HZ             |
| Lamp Life (Rated) .....      | 15,000 hours        |
| Minimum Starting Temp .....  | -22F/-30C           |
| Maximum Operating Temp ..... | 40°C                |
| CRI .....                    | 80                  |



**3 YEAR WARRANTY**  
\* Based on 12 hours use per day



A-Lamps  
60W/100W  
equivalent

BR30  
65W  
equivalent

PAR38  
90W  
equivalent

All Glass A-Lamp  
60W  
equivalent

G25  
40W  
equivalent

Deco  
40W  
equivalent

**LED**  
we know light.™





PRO Line LED Lamps  
15,000 HOURS • 3 YEAR WARRANTY

| ITEM #   | DESCRIPTION                     | VOLTAGE | WATTS | INCANDESCENT WATTS | LPW   | LUMENS | COLOR | HOURS  | CRI | MOL (inches) | DIA (inches) | BASE | WARRANTY YEARS |
|--|---------------------------------|---------|-------|--------------------|-------|--------|-------|--------|-----|--------------|--------------|------|----------------|
| <b>LED All Glass A-LAMP</b>                    |                                 |         |       |                    |       |        |       |        |     |              |              |      |                |
| <b>4.5W A19 • Dimmable • 15,000 Hour</b>       |                                 |         |       |                    |       |        |       |        |     |              |              |      |                |
| LFF40A19D1527K                                 | LED 40W EQ GLASS A19 DIM 27K FR | 120     | 4.5   | 40                 | 94.4  | 425    | 2700K | 15,000 | 80  | 4.2          | 2.4          | E26  | 3              |
| LFC40A19D1527K                                 | LED 40W EQ GLASS A19 DIM 27K CL | 120     | 4.5   | 40                 | 94.4  | 425    | 2700K | 15,000 | 80  | 4.2          | 2.4          | E26  | 3              |
| <b>5W A19 • Non-Dimmable • 15,000 Hour</b>     |                                 |         |       |                    |       |        |       |        |     |              |              |      |                |
| LFF40A19N1527K                                 | LED 40W EQ GLASS A19 ND 27K FR  | 120     | 5     | 40                 | 85.0  | 425    | 2700K | 15,000 | 80  | 4.2          | 2.4          | E26  | 3              |
| <b>8W A19 • Dimmable • 15,000 Hour</b>         |                                 |         |       |                    |       |        |       |        |     |              |              |      |                |
| LFF60A19D1527K                                 | LED 60W EQ GLASS A19 DIM 27K    | 120     | 8     | 60                 | 90.6  | 725    | 2700K | 15,000 | 80  | 4.2          | 2.4          | E26  | 3              |
| LFF60A19D1550K                                 | LED 60W EQ GLASS A19 DIM 50K    | 120     | 8     | 60                 | 90.6  | 725    | 5000K | 15,000 | 80  | 4.2          | 2.4          | E26  | 3              |
| LFC60A19D1527K                                 | LED 60W EQ GLASS A19 DIM 27K CL | 120     | 8     | 60                 | 90.6  | 725    | 2700K | 15,000 | 80  | 4.2          | 2.4          | E26  | 3              |
| <b>8W A19 • Non-Dimmable • 15,000 Hour</b>     |                                 |         |       |                    |       |        |       |        |     |              |              |      |                |
| LFF60A19N1527K                                 | LED 60W EQ GLASS A19 ND 27K     | 120     | 8     | 60                 | 90.6  | 725    | 2700K | 15,000 | 80  | 4.2          | 2.4          | E26  | 3              |
| LFF60A19N1550K                                 | LED 60W EQ GLASS A19 ND 50K     | 120     | 8     | 60                 | 90.6  | 725    | 5000K | 15,000 | 80  | 4.2          | 2.4          | E26  | 3              |
| <b>LED All Glass Decorative 40W Equivalent</b> |                                 |         |       |                    |       |        |       |        |     |              |              |      |                |
| <b>4W Deco • Dimmable • 15,000 Hour</b>        |                                 |         |       |                    |       |        |       |        |     |              |              |      |                |
| FG25D40V27W                                    | LED 4W G25 DIM 27K FR Pro       | 120     | 4     | 40                 | 87.5  | 350    | 2700K | 15,000 | 80  | 4.5          | 3.2          | E26  | 3              |
| FB11D40V27E12C                                 | LED 4W B11 DIM 27K E12 CL Pro   | 120     | 4     | 40                 | 87.5  | 350    | 2700K | 15,000 | 80  | 3.5          | 1.4          | E12  | 3              |
| <b>LED A-LAMP</b>                              |                                 |         |       |                    |       |        |       |        |     |              |              |      |                |
| <b>9W A19 • Dimmable • 15,000 Hour</b>         |                                 |         |       |                    |       |        |       |        |     |              |              |      |                |
| L60A19D15V27K                                  | LED 9W A19 DIM 2700K Pro        | 120     | 9     | 60                 | 88.9  | 800    | 2700K | 15,000 | 80  | 4.3          | 2.4          | E26  | 3              |
| <b>9W A19 • Non-Dimmable • 15,000 Hour</b>     |                                 |         |       |                    |       |        |       |        |     |              |              |      |                |
| L60A19N15V27K                                  | LED 9W A19 ND 2700K ProLine     | 120     | 9     | 60                 | 88.9  | 800    | 2700K | 15,000 | 80  | 4.3          | 2.4          | E26  | 3              |
| <b>14W A19 • Non-Dimmable • 15,000 Hour</b>    |                                 |         |       |                    |       |        |       |        |     |              |              |      |                |
| L100A19N15V27K                                 | LED 14W A19 DIM 2700K ProLine   | 120     | 14    | 100                | 107.1 | 1500   | 2700K | 15,000 | 80  | 4.5          | 2.6          | E26  | 3              |
| <b>15W A19 • Dimmable • 15,000 Hour</b>        |                                 |         |       |                    |       |        |       |        |     |              |              |      |                |
| L100A19D15V27K                                 | LED 15W A19 DIM 2700K Pro       | 120     | 15    | 100                | 100.0 | 1500   | 2700K | 15,000 | 80  | 4.5          | 2.6          | E26  | 3              |
| <b>LED BR</b>                                  |                                 |         |       |                    |       |        |       |        |     |              |              |      |                |
| <b>7.5W R20 • Dimmable • 15,000 Hour</b>       |                                 |         |       |                    |       |        |       |        |     |              |              |      |                |
| L50R20D15V27K                                  | LED 7W R20 DIM 2700K Proline    | 120     | 7.5   | 50                 | 66.7  | 500    | 2700K | 15,000 | 80  | 3.5          | 2.5          | E26  | 3              |
| <b>9W BR30 • Dimmable • 15,000 Hour</b>        |                                 |         |       |                    |       |        |       |        |     |              |              |      |                |
| L65BR30D15V27K                                 | LED 9W BR30 DIM 2700K Pro       | 120     | 9     | 65                 | 72.2  | 650    | 2700K | 15,000 | 80  | 4.8          | 3.7          | E26  | 3              |
| <b>14W BR40 • Dimmable • 15,000 Hour</b>       |                                 |         |       |                    |       |        |       |        |     |              |              |      |                |
| L75BR40D15V27K                                 | LED 14W BR40 DIM 2700K Proline  | 120     | 14    | 75                 | 76.1  | 1065   | 2700K | 15,000 | 80  | 5.6          | 7.3          | E26  | 3              |
| <b>LED PAR*</b>                                |                                 |         |       |                    |       |        |       |        |     |              |              |      |                |
| <b>7W PAR20 • Dimmable • 15,000 Hour</b>       |                                 |         |       |                    |       |        |       |        |     |              |              |      |                |
| L50P20D15V30KFL                                | LED 7W P20 DIM 30KFL Proline    | 120     | 7     | 50                 | 75    | 525    | 3000K | 15,000 | 80  | 3.4          | 2.3          | E26  | 3              |
| <b>9W PAR30 • Dimmable • 15,000 Hour</b>       |                                 |         |       |                    |       |        |       |        |     |              |              |      |                |
| L75P30D15V30KFL                                | LED 10W P30 DIM 30KFL Proline   | 120     | 9     | 75                 | 80    | 720    | 3000K | 15,000 | 80  | 4.8          | 3.9          | E26  | 3              |
| <b>13W PAR38 • Dimmable • 15,000 Hour</b>      |                                 |         |       |                    |       |        |       |        |     |              |              |      |                |
| L90P38D15V30KFL                                | LED 13W P38 DIM 30KFL Pro       | 120     | 13    | 90                 | 84.6  | 1100   | 3000K | 15,000 | 80  | 5.3          | 4.8          | E26  | 3              |

\* ALL PAR LAMPS HAVE A 40° BEAM ANGLE AND ARE SUITABLE FOR WET LOCATIONS.



**3** YEAR WARRANTY  
\* Based on 12 hours use per day



TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcp.com

©TCP MAY 2019/WF151042

For the most up-to-date specs, please visit [www.tcp.com](http://www.tcp.com)