

# LED LAMP

ARTISAN Series



## LED A15, A19, B10

Low Non Visible Flicker LOW non visible FLICKER



2-year limited warranty

Operating temperature range -20 °C ~ +40 °C



### Features & Benefits

- Reduced flicker down to 10%\*
  - Compare to 6.6% traditional incandescent
  - Far below California T20 standard 30%
  - Significantly improve light quality
  - Optimize eye comfort


With clear, amber or milky white glass cover

15,000 hour life (L70), high CRI (80+), dimmable

Damp location rated

\*Except AR-A19LF/8W & AR-A19LNVF/8W

### Dimensional Drawing



### Ordering Information Example: AR-A15LF/5W/30/D/C

Family Name	Lamp Type	Wattage	CCT	Dimmable	Cover
AR (Artisan)	A15LF (A15, Low flicker)	5W	22 (2200K)	D (Dimmable)	C (Clear) A (Amber) MW (Milky white)
	A19LNVF/ A19LF (A19, Low flicker)	8W	27 (2700K)		
	B10LNVF/ B10LF (B10, Low flicker)		30 (3000K)		
			40 (4000K)		

### Product Specification

Ordering Code	Energy Star	Model Number	Product Description	Watts (W)	Replacement Filament	Replacement Incandescent	Base	Voltage (V)	Hour Rating	Beam Angle	Initial Lumens (lm)	CCT(K)	CRI	Damp Loc.	M.O.L. (inch)	Case QTY.
1771209	-	AR-A15LF/5W/30/D/C	A15 Low Flicker 5W 30K Dimmable Clear	5	-	40W	E26	120	15,000	330°	500	3000	80	Y	3.54	40
1771213	-	AR-A15LF/5W/30/D/MW	A15 Low Flicker 5W 30K Dimmable Milky white	5	-	40W	E26	120	15,000	330°	450	3000	80	Y	3.54	40
1771210	-	AR-A15LF/5W/30/D/F	A15 Low Flicker 5W 30K Dimmable Milky white	5	-	40W	E26	120	15,000	330°	450	3000	80	Y	3.54	40
1772110	-	AR-A19LF/8W/27/D/C	A19 Low Flicker 8W 27K Dimmable Clear	8	-	60W	E26	120	15,000	330°	800	2700	80	Y	4.29	40
1772202	-	AR-A19LF/8W/30/D/C	A19 Low Flicker 8W 30K Dimmable Clear	8	-	60W	E26	120	15,000	330°	800	3000	80	Y	4.29	40
1772205	-	AR-A19LF/8W/30/D/MW	A19 Low Flicker 8W 30K Dimmable Milky white	8	-	60W	E26	120	15,000	330°	750	3000	80	Y	4.29	40
1772115	-	AR-A19LNVF/8W/27/D/C	A19 Low Flicker New Generation 8W 27K Dimmable Clear	8	-	60W	E26	120	15,000	330°	800	2700	80	Y	4.29	20
1772207	-	AR-A19LNVF/8W/30/D/C	A19 Low Flicker New Generation 8W 30K Dimmable Clear	8	-	60W	E26	120	15,000	330°	800	3000	80	Y	4.29	20
1771149	-	AR-B10LNVF/5W/27/E12/D/C	B10 Low Flicker New Generation 5W 27K E12 Dimmable Clear	5	-	60W	E12	120	15,000	330°	500	2700	80	Y	3.78	50
1771223	-	AR-B10LNVF/5W/30/E12/D/C	B10 Low Flicker New Generation 5W 30K E12 Dimmable Clear	5	-	60W	E12	120	15,000	330°	500	3000	80	Y	3.78	50
1771229	Yes	AR-B10LF/5W/30/E12/D/C/ES	B10 Low Flicker 5W 30K E12 Dimmable Clear Energy Star	5	-	60W	E12	120	15,000	330°	500	3000	80	Y	3.78	96
1771222	-	AR-B10LF/5W/30/E12/D/MW	B10 Low Flicker 5W 30K E12 Dimmable Milky white	5	-	60W	E12	120	15,000	330°	450	3000	80	Y	3.78	50
1771406	-	AR-B10LNVF/5W/40/E12/D/C	B10 Low Flicker New Generation 5W 40K E12 Dimmable Clear	5	-	60W	E12	120	15,000	330°	500	4000	80	Y	3.78	50
1771930	-	AR-B10LNVF/5W/22/E12/D/A	B10 Low Flicker New Generation 5W 22K E12 Dimmable Amber	5	60W	-	E12	120	15,000	330°	450	2200	80	Y	3.78	50
1771150	-	AR-B10LNVF/5W/27/D/C	B10 Low Flicker New Generation 5W 27K E26 Dimmable Clear	5	-	60W	E26	120	15,000	330°	500	2700	80	Y	3.78	50