

# LED LAMP ARTISAN

**LOW**  
non visible  
**FLICKER**

**G16.5, G30, G40**



## Features & Benefits

Reduced flicker down to 10%

- Compare to 6.6% traditional incandescent
- Far below California T20 standard 30%
- Significantly improve light quality
- Optimize eye comfort


With clear, amber or milky white glass cover

Dimmable, High CRI (80+)

15,000 hour average life span

Rated for damp locations

## Dimensional drawing



## Warranty & Cautions

2-year limited warranty

Operating temperature range between -20°C and +40°C

## Ordering Information

Example: AR-A19LF/8W/30/D/MW

LED CLASS	LAMP TYPE	WATTAGE	CCT(K)	BASE	DIMMABLE	COVER
AR (Artisan)	G16.5LF (Low Flicker), G16.5 G30LF (Low Flicker), G30 G40LF (Low Flicker), G40	4W 5W 6W	22 (2200K) 27 (2700K) 30 (3000K)	E12 (E12) Blank (E26)	D (dimmable)	C (Clear) A (Amber) MW (Milky White)

## Product Specification

Ordering Code	Model Number	Product Description	Watts (W)	Replacement Filament	Replacement Incandescent	Base	Voltage (V)	Hour Rating	Beam Angle	Initial Lumens (lm)	CCT(K)	CRI	Damp LOC.	M.O.L. (inch)	Case QTY.
1771146	AR-G16.5LF/4W/27/E12/D/C	G16.5 Low Flicker 4W 27K E12 Dimmable Clear	4	-	40W	E12	120	15,000	330	350	2700	80	Y	3.31	50
1771208	AR-G16.5LF/4W/30/E12/D/C	G16.5 Low Flicker 4W 30K E12 Dimmable Clear	4	-	40W	E12	120	15,000	330	350	3000	80	Y	3.31	50
1771212	AR-G16.5LF/4W/30/E12/D/MW	G16.5 Low Flicker 4W 30K E12 Dimmable Milky white	4	-	40W	E12	120	15,000	330	300	3000	80	Y	3.31	50
1771109	AR-G16.5/4W/27/D/C	G16.5 4W 27K E26 Dimmable Clear	4	-	40W	E26	120	15,000	330	350	2700	80	Y	3.31	50
1771216	AR-G30LF/5W/30/D/MW	G30 Low Flicker 5W 30K Dimmable Milky white	5	-	50W	E26	120	15,000	330	450	3000	80	Y	5.28	40
1772112	AR-G30/6W/27/D/C	G30 6W 27K Dimmable Clear	6	-	60W	E26	120	15,000	330	600	2700	80	Y	5.28	40
1771143	AR-G30/6W/30/D/C	G30 6W 30K Dimmable Clear	6	-	60W	E26	120	15,000	330	600	3000	80	Y	5.28	40
1772113	AR-G30/6W/27/D/F	G30 6W 27K Dimmable Frost	6	-	60W	E26	120	15,000	330	600	2700	80	Y	5.28	40
1771903	AR-G30/5W/22/D/A	G30 5W 22K Dimmable Amber	5	60W	-	E26	120	15,000	320	400	2200	80	Y	5.31	40
1771217	AR-G40LF/4W/30/D/C	G40 Low Flicker 4W 30K Dimmable Clear	4	-	40W	E26	120	15,000	330	350	3000	80	Y	6.77	8
1771218	AR-G40LF/4W/30/D/MW	G40 Low Flicker 4W 30K Dimmable Milky White	4	-	40W	E26	120	15,000	330	320	3000	80	Y	6.77	8
1771909	AR-G40/5W/22/D/A	G40 5W 22K Dimmable Amber	5	60W	-	E26	120	15,000	320	400	2200	80	Y	6.69	12