




## VIV-G9, VIV-G4, VIV-MR11

### Features & Benefits

High lumen design	25,000 hour average life*
High CRI ≥80	Enclosed luminaires application*
cETL listed, FCC compliant, RoHS compliant	Damp location approved*
Dimmable, except MR11	* For applicable models, see product specification below

### Dimensional drawing



### Warranty & Cautions

15,000hrs: 2-year; 25,000hrs: 3-year limited warranty  
 Operating temperature range between -20°C and +40°C

### Product Specification

Ordering Code	Model Number	Watts	Replacement Halogen	Base	Voltage (V)	Hour Rating	Beam Angle	Initial Lumens(lm)	CCT(K)	CRI	Enclosed Fixture	Damp Location	M.O.D. (inch)	M.O.L. (inch)	Case QTY.
1751100	VIV-G9/4W/27/D	4	45W	G9	120	25,000	330°	450	2700	80	Y	Y	0.77	2.16	100
1751200	VIV-G9/4W/30/D	4	45W	G9	120	25,000	330°	450	3000	80	Y	Y	0.77	2.16	100
1751400	VIV-G9/4W/40/D	4	45W	G9	120	25,000	330°	450	4000	80	Y	Y	0.77	2.16	100
1751201	VIV-G4/2.5W/30/D	2.5	30W	G4	12	15,000	360°	300	3000	80	N	N	0.52	1.7	100
1751403	VIV-G4/2.5W/40/D	2.5	30W	G4	12	15,000	360°	300	4000	80	N	N	0.52	1.7	100
1761244	VIV-MR11/3W/30/FL/GU4	3	20W	GU4	12	25,000	30°	200	3000	80	Y	Y	-	1.5	100

### Ordering Information Example: VIV-G9/4W/27/D

LED CLASS	LAMP TYPE	WATTAGE	CCT (K)	DIMMABLE	COVER
VIV (Vivid)	G9	4W (G9)	27 (2700K)	D (dimmable)	FL (Flood)
	G4	2.5W (G4)	30 (3000K)		
	MR11	3W (MR11)	40 (4000K)		