

E11/4.5W



FR-E11-4.5W-019DIM	
Product Size	Φ18.2*51mm
Power	4.5W
LED Quantity	52pcs
Net weight	13.3g
LED type	SMD LED 2835
Luminous Efficiency	450-500lm
Beam angle	360°
Input Voltage	AC120V 60Hz
Power Factor	>0.9
Rendering Index	>80
IP Grade	IP20
CCT(K)	3000K
Certification	ETL
Storage temperature	-25°C~+65°C
Operating temperature	-20°C~+45°C (the best in 25°C)
Environment humidity	40-90%RH
Life Span	25000hrs
Quality Warranty	3years



R7s/5W



FR-R7s-5W-016DIM	
Product Size	Φ18*78mm
Power	5W
LED Quantity	70pcs
Net weight	14.8g
LED type	SMD LED 2835
Luminous Efficiency	670-700lm
Beam angle	360°
Input Voltage	AC120V 60Hz
Power Factor	>0.9
Rendering Index	>80
IP Grade	IP20
CCT(K)	3000K
Certification	ETL
Storage temperature	-25°C~+65°C
Operating temperature	-20°C~+45°C (the best in 25°C)
Environment humidity	40-90%RH
Life Span	25000hrs
Quality Warranty	3years



R7s/9W



FR-R7s-9W-004DIM	
Product Size	Φ18*118mm
Power	9W
LED Quantity	72pcs
Net weight	24g
LED type	SMD LED 2835
Luminous Efficiency	1100-1200lm
Beam angle	360°
Input Voltage	AC120V 60Hz
Power Factor	>0.9
Rendering Index	>80
IP Grade	IP20
CCT(K)	3000K
Certification	ETL
Storage temperature	-25°C~+65°C
Operating temperature	-20°C~+45°C (the best in 25°C)
Environment humidity	40-90%RH
Life Span	25000hrs
Quality Warranty	3years

